



akcihan

Technical Data Sheet

Pink Fused Aluminum Oxide

Pink aluminum oxide is a special type of aluminum oxide (Al₂O₃). It occurs naturally in a pink color and is produced with high purity. It is based on the crystalline structure of aluminum oxide. Widely used in the sandblasting industry, pink aluminum oxide is a material known for its durability. It exhibits high resistance to high temperatures and chemicals. With its high surface hardness and resistance to friction, it is commonly used for surface preparation, cleaning, and smoothing in sandblasting processes. Additionally, it is favored for its aesthetic appeal in decorative applications.

Applications

- Sandblasting
- Grinding – Metal preparation
- Refractory
- Sandpaper – Cloth and Polishing

Available Sizes

Fepa Standards	Micron (µm)
F008	2000 - 2800
F010	1700 - 2360
F012	1400 - 2000
F014	1180 - 1700
F016	1000 - 1400
F020	850 - 1180
F022	710 - 1000
F024	600 - 850
F030	500 - 710
F036	425 - 600
F040	355 - 500
F046	300 - 425
F054	250 - 355
F060	212 - 300
F070	180 - 250
F080	150 - 212
F090	125 - 180
F100	106 - 150
F120	90 - 125
F150	63 - 106
F180	63 - 90
F220	53 - 75

Chemical Analysis

Compound	Percent (%)
Al ₂ O ₃	99,30
Cr ₂ O ₃	0,30
Fe ₂ O ₃	0,05
Na ₂ O	0,30
CaO	0,05

Physical Properties

Sertlik	9 Mohs
Şekil	Angular
Erime Noktası	~ 2050 °C
Yoğunluk	3,9 - 4,1 g/cm ³
Kitle Yoğunluğu	1,3 – 2,0 g/cm ³

Packaging

25kg Kraft bags on pallet of 1 ton

Akcihan Cam San. Tic. Ltd. Şti

Yenidoğan Mh. Polat Sk. No:17

Bayrampaşa / İstanbul / Türkiye

www.camkumu.com 90 212 595 00 17